

09/20/00
928jc U.S. PTO

SIDLEY & AUSTIN
A PARTNERSHIP INCLUDING PROFESSIONAL CORPORATIONS

CHICAGO
LOS ANGELES
NEW YORK
WASHINGTON, D.C.

717 NORTH HARWOOD
DALLAS, TEXAS 75201
TELEPHONE 214 981 3300
FACSIMILE 214 981 3400

HONG KONG
LONDON
SHANGHAI
SINGAPORE
TOKYO

FOUNDED 1866

WRITER'S DIRECT NUMBER
(214) 981-3328

WRITER'S E-MAIL ADDRESS
pplap@sidley.com

928jc U.S. PTO
09/20/00

September 20, 2000

BOX PATENT APPLICATION
Assistant Director For Patents
Washington, D.C. 20231

EXPRESS MAIL MAILING LABEL NO.: EL195376344US
DATE OF DEPOSIT SEPTEMBER 20, 2000
I hereby certify that this paper or fee is being deposited with the United States Postal Service "Express Mail Post Office to Addressee" service under 39 C.F.R. § 110 on the dated indicated above and is addressed to BOX PATENT APPLICATION, Assistant Director for Patents, Washington, DC 20231.

Derrick T. Gordon
Name of Person Mailing Paper or Fee

Derrick T. Gordon
Signature

September 20, 2000
Date of Signature

Re: New U.S. Patent Application
LIGHT SHUTTER DEVICE AND A DRIVING METHOD THEREOF
By: Tsukasa YAGI, Ken MATSUBARA, Tatsuya KANAZAWA, and
Tomohiko MASUDA
Attorney Docket: 15162/02500

Dear Sir:

Enclosed for filing are the following papers relating to
LIGHT SHUTTER DEVICE AND A DRIVING METHOD THEREOF, Tsukasa YAGI,
Ken MATSUBARA, Tatsuya KANAZAWA, and Tomohiko MASUDA, inventors:

- (1) Specification (20 pages, including 18 claims and an abstract);
- (2) Unexecuted Declaration and Power of Attorney (9 pages);

Assistant Director For Patents
 September 20, 2000
 Page 2

- (3) Formal Drawings (11 sheets);
- (4) Transmittal letter (2 pages) with PrintEFS Patent Application Bibliographic Data (2 pages); and
- (5) Transmittal letter (2 pages) with certified copy of priority document (27 pages).

The amount of the filing fee is calculated below:

			Fee for small entity			Fee for other than small entity	
Fee	No. filed	No. extra *	Rate	Fee	OR	Rate	Fee
Basic fee				\$345	OR		\$690
Total claims	9-20=	0	X \$9=	\$0	OR	X \$18=	\$-0-
Independent claims	2-3=	0	X \$39=	\$0	OR	X \$78=	\$-0-
Multiple Dependent Claim Presented	0	0	+\$130=	\$0	OR	+\$260=	\$-0-
Total				\$0	OR	Total	\$690.00

*If the difference in Column 1 is less than zero, enter "0" in Column 2.

Please charge the required fee of \$690.00 for the application filing fee to Sidley & Austin's Deposit Account No. 18-1260. If additional fees are due, please charge any fees required during the pendency of this application (other than the issue fee) to Deposit Account No. 18-1260. Please credit any overpayment to Deposit Account No. 18-1260.

This transmittal letter is being filed in duplicate.

SIDLEY & AUSTIN

DALLAS

Assistant Director For Patents
September 20, 2000
Page 3

All correspondence is to be directed to the Applicants' attorney at the Dallas address listed above.

Respectfully submitted,

By: James W. Williams
James W. Williams
Registration No. 20,047
Attorney for Applicants

JWW:pm
Enclosures

INVENTOR INFORMATION

Inventor One Given Name:: Tsukasa

Family Name:: YAGI

Postal Address Line One:: Minolta Co., Ltd., Osaka Kokusai Bldg.,

Postal Address Line Two:: 3-13, 2-Chome, Azuchi-Machi, Chuo-Ku

City:: Osaka-Shi

State or Province:: Osaka

Country:: JAPAN

Postal or Zip Code:: 541-8556

City of Residence:: Osaka-Shi

State or Province of Residence:: Osaka

Country of Residence:: JAPAN

Citizenship Country:: JAPAN

Inventor Two Given Name:: Ken

Family Name:: MATSUBARA

Postal Address Line One:: Minolta Co., Ltd., Osaka Kokusai Bldg.

Postal Address Line Two:: 3-13, 2-Chome, Azuchi-Machi, Chuo-ku

City:: Osaka-Shi

State or Province:: Osaka

Country:: JAPAN

Postal or Zip Code:: 541-8556

City of Residence:: Osaka-Shi

State or Province of Residence:: Osaka

Country of Residence:: JAPAN

Citizenship Country:: JAPAN

Inventor Three Given Name:: Tatsuya

Family Name:: KANAZAWA

Postal Address Line One:: Minolta Co., Ltd., Osaka Kokusai Bldg.,

Postal Address Line Two:: 3-13, 2-Chome, Azuchi-Machi, Chou-Ku

City:: Osaka-Shi

State or Province:: Osaka

Country:: JAPAN

Postal or Zip Code:: 541-8556

City of Residence:: Osaka-Shi

State or Province of Residence:: Osaka

Country of Residence:: JAPAN

Citizenship Country:: JAPAN

Inventor Four Given Name:: Tomohiko

Family Name:: MASUDA

Postal Address Line One:: Minolta Co., Ltd., Osaka Kokusai Bldg.,

Postal Address Line Two:: 3-13, 2-Chome, Azuchi-Machi, Chou-Ku

City:: Osaka-Shi

State or Province:: Osaka

Country:: JAPAN

Postal or Zip Code:: 541-8556

City of Residence:: Osaka-Shi

State or Province of Residence:: Osaka

Country of Residence:: JAPAN

Citizenship Country:: JAPAN

CORRESPONDENCE INFORMATION

Correspondence Customer Number:: 24367
Telephone One:: 214-981-3328
Fax One:: 214-981-3400
Electronic Mail One:: pplap@sidley.com
Telephone Two:: 214-981-3300
Electronic Mail Two:: jwilli09@sidley.com

APPLICATION INFORMATION

Title Line One:: LIGHT SHUTTER DEVICE AND A DRIVING METHO
Title Line Two:: D THEREOF
Total Drawing Sheets:: 11
Formal Drawings?:: Yes
Application Type:: Utility
Docket Number:: 15162/02500
Secrecy Order in Parent Appl.?:: No

REPRESENTATIVE INFORMATION

Representative Customer Number:: 24367

PRIOR FOREIGN APPLICATIONS

Foreign Application One:: 11-266829
Filing Date:: 09-21-1999
Country:: JAPAN
Priority Claimed:: Yes

Source:: PrintEFS Version 1.0.1

LIGHT SHUTTER DEVICE AND A DRIVING METHOD THEREOF

This application is based on application No. 11-266829 filed in Japan, the content of which is hereby incorporated by reference.

5

BACKGROUND OF THE INVENTION

1. Field of the Invention

10 The present invention relates to a light shutter device and a driving method thereof, and more particularly to a light shutter device which has light shutter elements made of a material with an electro-optical effect such as PLZT to write an image on a photosensitive recording medium and a method of driving such a device.

2. Description of Related Art

15 As means of writing an image (latent image) on a silver salt photographic paper or film or on a photosensitive member for electrophotography, there have been suggested various kinds of light shutter devices which employ light shutter elements made of a material with an electro-optical effect such as PLZT and which turn on and off
20 the light shutter elements individually.

In such a light shutter device, when a voltage is applied to a PLZT light shutter element, the PLZT causes birefringence, and light which is incident to the element via a polarizer located before the element is emergent from an analyzer located after the element. The polarizer and
25 the analyzer are arranged to cross Nicol (are arranged in such a way that the direction of polarization of the polarizer and the direction of

polarization of the analyzer will cross at 90 degrees to each other). The plane of polarization of the polarizer and the plane of polarization of the analyzer are at 45 degrees to the direction of electric field acting on the light shutter element.

5 In order to write a full-color image, color filters of R, G and B, which are the three primary colors, are switched in order during irradiation of the light shutter elements, so that a silver salt film is exposed to light of R, light of G and light of B separately line by line.

10 Incidentally, as Fig. 11 shows, with respect to a light shutter element made of PLZT, the relationship between light transmittance and voltage applied thereto changes according to whether the light is of red, green or blue. The voltage to achieve the maximum light transmittance is referred to as a half-wave voltage. Supposing that the half-wave voltages for red light, for green light and for blue light are V_r , V_g and V_b respectively, $V_r > V_g > V_b$. In order to obtain a full-color image of high
15 quality, the driving voltage of the light shutter elements shall be switched to V_r , V_g and V_b for red, green and blue, respectively.

20 In Japanese Patent Laid Open Publication No. 10-333107, the Japanese applicants suggested a device which switches the voltage applied to the driver IC for the light shutter elements in synchronization with the light incidence of the three primary colors. However, the switching of a high voltage to be applied to the driver IC is influenced by the capacity of a bypass capacitor or the like, it is difficult to switch the voltage at a high speed.

25

SUMMARY OF THE INVENTION

An object of the present invention is to provide a light shutter device in which the driving voltage of light shutter elements can be
5 speedily switched between values suitable for light of the three primary colors and a method of driving such a device.

Another object of the present invention is to provide a light shutter device in which not only the above object can be achieved but also variation of the half-wave voltages during continuous long-time
10 operation is minimized so as to obtain fixed light transmittance and a method of driving such a device.

Further, another object of the present invention is to provide a light shutter device in which not only the above objects can be achieved but also the driving voltage of light shutter elements has a good rising
15 characteristic and a method of driving such a device.

In order to attain the objects, a light shutter device according to the present invention comprises: a light source which emits light of a plurality of colors switching from one to another in order; a plurality of light shutter elements made of a material with an electro-optical effect,
20 said light shutter elements controlling in accordance with image data whether to transmit or not to transmit the light which has been emitted from the light source and is incident to the light shutter elements; and a driver for driving the light shutter elements, said driver altering a driving condition in synchronization with switch of the colors of the light source.

25 In the light shutter device according to the present invention, light of a plurality of colors is incident to a plurality of the light shutter

elements with the colors switched from one to another in order, and a driving voltage is applied between each individual electrode and a common electrode in accordance with image data. In synchronization with switch of the colors, a driving condition of the light shutter elements is altered. Specifically, to the individual electrodes, a voltage is applied fixedly during radiation of light of all the three primary colors. The voltage is, for example, the highest of the respective half-wave voltages for red, green and blue, that is, the half-wave voltage V_r for red. On the other hand, to the common electrode, in synchronization with color switch away R, G and B, optimal voltage for the colors, for example, 0V, V_r-V_g and V_r-V_b are applied.

In the driving method according to the present invention, merely by altering the potential of the common electrode within a low level, the voltage applied to the light shutter elements can be switched between optimal voltages (half-wave voltages) for the three primary colors at a high speed. Consequently, a full-color image of high quality can be formed.

In the light shutter device according to the present invention, preferably, the electric field acting on the light shutter elements is inverted at specified cycles. If a unidirectional electric field continuously acts on the light shutter elements, fatigue of the light shutter elements occurs, that is, the half-wave voltages of the light shutter elements vary. By inverting the electric field at specified cycles, such fatigue can be prevented.

Moreover, in the light shutter device according to the present invention, it is preferred to superimpose a spike pulse voltage at a start of

applying a driving voltage to the light shutter elements. Thereby, the rising characteristic of the driving voltage can be improved, which brings a possibility of lowering the driving voltage and improves the picture quality.

5

BRIEF DESCRIPTION OF THE DRAWINGS

These and other objects and features of the present invention will be apparent from the following description with reference to the accompanying drawings, in which:

Fig. 1 is a schematic view of a light shutter device according to the present invention;

Fig. 2 is a block diagram which shows a driving circuit of the light shutter device;

Fig. 3 is a block diagram which shows a high-voltage driver and a common electrode driving circuit included in the circuit shown by Fig. 2;

Fig. 4 is a timing chart which shows operation of the driving circuit;

Fig. 5 is a timing chart which shows a first embodiment of a driving method according to the present invention;

Fig. 6 is a timing chart which shows a second embodiment of a driving method according to the present invention;

Fig. 7 is a timing chart which shows a third embodiment of a driving method according to the present invention;

Fig. 8 is a timing chart which shows a fourth embodiment of a driving method according to the present invention;

Fig. 9 is a timing chart which shows a fifth embodiment of a driving method according to the present invention;

Fig. 10 is a timing chart which shows a sixth embodiment of a driving method according to the present invention; and

5 Fig. 11 is a graph which shows the relationships between driving voltage applied to a light shutter element and red light transmittance, between driving voltage and green light transmittance and between driving voltage and blue light transmittance.

10 DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Embodiments of a light shutter device and a driving method thereof are described with reference to the accompanying drawings.

Structure of Light Shutter Device

15 Referring to Fig. 1, a light shutter device according to the present invention is described. This device comprises a light source (halogen lamp) 1, a heat filter 2, a color filter 3, an optical fiber array 4, a polarizer 5, a light shutter module 6, an analyzer 7 and an imaging lens array 8.

The color filter 3 is a rotary disk which has three filter sections
20 which transmit light of the three primary colors, namely, R, G and B, respectively. The color filter 3 is driven to rotate in synchronization with one-line writing by use of light shutter elements, which will be described later. The optical fiber array 4 is a bundle of a large number of optical fibers. Light emitted from the light source 1 is incident to the optical
25 fiber array 4 through its incidence end 4a via the heat filter 2 and is emergent therefrom linearly through the other end 4b. The polarizer 5

and the analyzer 7 are arranged to cross Nicol, and the plane of polarization of the polarizer 5 and the plane of polarization of the analyzer 7 are at 45 degrees to the direction of electric field applied to the light shutter elements.

5 The light shutter module 6 has a plurality of PLZT light shutter chips 12 and a plurality of driving circuits 13 on a ceramic substrate 11 with a slit or a glass substrate. In each of the light shutter chips 12, a large number of light shutter elements, each of which corresponds to a pixel, are formed. As Fig. 2 shows, the light shutter elements 41 are
10 arranged in two rows alternately, and the two rows of light shutter elements 41 form one line in a main scanning direction.

PLZT, as is well known, is a light-transmitting ceramic material which has a large Kerr constant and an electro-optical effect. Light which is polarized linearly by the polarizer 5 is incident to each of the
15 light shutter elements 41. At this time, when the voltage applied to the light shutter element 41 is turned on, the plane of polarization is rotated, and the light is emergent from the analyzer 7. When the voltage is off, the plane of polarization is not rotated, and the light is cut by the analyzer 7.

20 Thus, by turning on and off the voltages applied to the light shutter elements 41 individually, the light is transmitted or cut pixel by pixel, and the light emergent from the analyzer 7 is imaged on a photosensitive member (not shown) via the imaging lens array 8. The light shutter elements 41 are turned on and off in accordance with image
25 data (main scanning) line by line, while the photosensitive member is moved in a direction (sub scanning), and thereby, a two-dimensional

image is formed on the photosensitive member.

Driving Circuit

As Fig. 2 shows, each of the driving circuits 13 comprises a shift register 31, a latch circuit 32, a gate circuit 33, a high-voltage driver 34 and a common electrode driving circuit 35. Individual electrodes 43 for the respective light shutter elements 41 are connected to the high-voltage driver 34, and a common electrode 42 is grounded via the common electrode driving circuit 35. The high-voltage driver 34, as Fig. 3 shows, has two switching elements 45 and 46. When the switching element 45 is turned on, a driving voltage is applied to the individual electrodes 43 of the light shutter elements 41. When the switching element 46 is turned on, the individual electrodes 43 are grounded.

Referring back to Fig. 2, image data for one line are transmitted to the shift register 31 in synchronization with a shift clock and latched in the latch circuit 32 in response to turning-on of a latch signal. When a gate signal is on, the image data are transmitted to the high-voltage driver 34 together with an inversion signal. When the inversion signal is off (non-inversion), a driving voltage is applied to the individual electrodes 43. When the inversion signal is on (inversion), the individual electrodes 43 are grounded.

The common electrode driving circuit 35 comprises a high-speed/high-voltage amplifier which amplifies a driving waveform inputted thereto with a specified gain. In this embodiment, the amplifier amplifies the inversion signal to the level of the driving voltage and applies the amplified signal to the common electrode 42. The common electrode driving circuit 35, at the time of non-inversion, grounds

the common electrode 42 and, at the time of inversion, applies a driving voltage to the common electrode 42.

With the driving circuit 13 of this structure, when the inversion signal is off, the common electrode 42 has the ground potential, and in this state, by applying a driving voltage to the individual electrodes 43, the light shutter elements 41 are turned on. The electric field at this time is referred to as a normal electric field (non-inverted electric field). On the other hand, when the inversion signal is on, the individual electrodes 43 have the ground potential, and in this state, by applying a driving voltage to the common electrode 42, the light shutter elements 41 are turned on. The electric field at this time is referred to as a reverse electric field (inverted electric field).

Fig. 4 is a timing chart which shows switching of the electric field. In the example of Fig. 4, the inversion signal is switched on and off for every one-line writing. As is well known, if a unidirectional electric field is continuously applied to the PLZT light shutter elements 41, a fatigue phenomenon occurs, that is, the half-wave voltages shift. However, by inverting the electric field at specified cycles, the fatigue phenomenon can be prevented. In the example of Fig. 4, the non-inversion/inversion rate is 50/50. This rate can be arbitrarily designed; however, by switching the electric field between non-inversion and inversion at a rate of 50 to 50, the shift of the half-wave voltages of the light shutter elements 41 can be effectively suppressed.

In the example of Fig. 4, at the time of inversion, the inversion signal is amplified so that a voltage equal to the driving voltage applied to the individual electrodes 43 at the time of non-inversion can be applied to

the common electrode 42. It is, however, possible to apply a desirable voltage to the common electrode 42 by changing the driving waveform. An electric field with a strength corresponding to the potential difference between the individual electrodes 43 and the common electrode 42 acts on
5 the light shutter elements 41.

This driving method in which the electric field applied to the light shutter elements 41 is inverted at specified cycles are referred to as an electric field inversion method. On the other hand, it is possible to drive the light shutter elements 41 by applying a driving voltage to the
10 individual electrodes 43 while connecting the common electrode 42 to the ground at all times. This driving method is referred to as a unidirectional electric field method.

First Embodiment of Driving Method

As Fig. 5 shows, in the first embodiment, the unidirectional
15 electric field method is adopted, and the voltage applied to the common electrode is altered.

First, the high-voltage driver which drives the individual electrodes is set to apply the highest voltage V_r of the half-wave voltages V_r , V_g and V_b (see Fig. 11) for the colors R, G and B. The voltage applied
20 to the common electrode is switched between 0V, $V_r - V_g$ and $V_r - V_b$ in synchronization with switching between R, G and B.

Thereby, to the light shutter elements, the voltage V_r is applied in writing R data, the voltage V_g is applied in writing G data, and the voltage V_b is applied in writing B data. In this way, high-speed voltage
25 switch is possible.

In the pixels in which the image data are 0 (when the

corresponding light shutter elements are to be turned off), voltages of V_g - V_r and V_b - V_r are applied to the light shutter elements in the duration of G data writing and in the duration of B data writing, respectively. However, as is apparent from Fig. 11, the voltages of V_g - V_r and V_b - V_r are
5 at most approximately 10V, and the light shutter elements supplied with the voltages of this extent transmit substantially no light.

Second Embodiment

As Fig. 6 shows, in the second embodiment, the electric field inversion method is adopted, and the voltage applied to the common
10 electrodes is altered.

When a non-inverted electric field is to act, the voltage application is carried out in the same way as described in the first embodiment. When an inverted electric field is to act, to the high-voltage driver which drives the individual electrodes, the highest voltage V_r of the half-wave
15 voltages V_r , V_g and V_b for the colors R, G and B is applied. Also, the inversion signal is turned on, so that the polarity of image data is inverted. The voltage applied to the common electrode is switched between V_r , V_g and V_b in synchronization with switching between R, G and B.

20 Thereby, to the light shutter elements, a voltage of $-V_r$ is applied in writing R data, a voltage of $-V_g$ is applied in writing G data and a voltage of $-V_b$ is applied in writing B data. In this way, high-speed voltage switch is possible.

In the pixels in which the image data are 0 (when the
25 corresponding light shutter elements are to be turned off), voltages of V_r - V_g and V_r - V_b are applied to the light shutter elements in the duration of

G data writing and in the duration of B data writing, respectively. However, as has been described in the first embodiment, the voltages cause substantially no problems.

Third Embodiment

5 As Fig. 7 shows, in the third embodiment, the unidirectional electric field method is adopted as in the first embodiment, and a spike pulse voltage is superimposed.

At the time of starting application of a driving voltage, a spike pulse voltage is applied. The waveform of the spike pulse voltage shall
10 be designed to have a voltage within a range from 5V to 30V and to have a pulse width within a range from $0.1 \mu \text{ sec.}$ to $10 \mu \text{ sec.}$ in accordance with the specification of the light shutter module. By superimposing a spike pulse voltage in synchronization with a start of driving voltage application, the rising characteristic of the driving voltage can be
15 improved, and it becomes possible to set the driving voltage to a lower value.

Fourth Embodiment

As Fig. 8 shows, in the fourth embodiment, the electric field inversion method is adopted as in the second embodiment, and a spike
20 pulse voltage is superimposed. The spike pulse is designed and is superimposed in the same way as described in the third embodiment.

Fifth Embodiment

As Fig. 9 shows, in the fifth embodiment, the unidirectional electric field method is adopted as in the first embodiment, and to the
25 high-voltage driver which drives the individual electrodes, the voltage V_b which is the half-wave voltage for light of B, not the voltage V_r , is applied.

The voltage applied to the common electrode is switched between V_b - V_r , V_b - V_g and 0V in synchronization with switching between R, G and B.

Thereby, to the light shutter elements, the voltage V_r is applied in writing R data, the voltage V_g is applied in writing G data and the voltage
5 V_b is applied in writing B data. In this way, high-speed voltage switch is possible.

In the pixels in which the image data are 0, to the corresponding light shutter elements, a voltage of V_r - V_b is applied in the duration of R data writing, and a voltage of V_g - V_b is applied in the duration of G data
10 writing. However, as has been described in connection with the first embodiment, the voltages cause substantially no problems.

Sixth Embodiment

As Fig. 10 shows, in the sixth embodiment, the unidirectional electric field is adopted as in the first embodiment, and to the high-
15 voltage driver which drives the individual electrodes, the half-wave voltage V_g for light of G, not the voltage V_r , is applied. The voltage applied to the common electrode is switched between V_g - V_r , 0V and V_g - V_b in synchronization with switching between R, G and B.

Thereby, to the light shutter elements, the voltage V_r is applied in
20 writing R data, the voltage V_g is applied in writing G data, and the voltage V_b is applied in writing B data. In this way, high-speed voltage switch is possible.

In the pixels in which image data are 0, to the corresponding light shutter elements, a voltage of V_r - V_g is applied in the duration of R data
25 writing, and a voltage of V_b - V_g is applied in the duration of B data writing. However, as has been described in connection with the first

embodiment, the voltages cause substantially no problems.

Other Embodiments

Although the present invention has been described in connection
with the preferred embodiments above, it is to be noted that various
5 changes and modifications are possible to those who are skilled in the art.
Such changes and modifications are to be understood as being within the
scope of the invention.

WHAT IS CLAIMED IS:

1. A light shutter device comprising:

a light source which emits light of a plurality of colors switching

5 from one to another in order;

a plurality of light shutter elements made of a material with an electro-optical effect, said light shutter elements controlling in accordance with image data whether to transmit or not to transmit the light which has been emitted from the light source and is incident to the light shutter

10 elements; and

a driver for driving the light shutter elements, said driver altering a driving condition in synchronization with switch of the colors of the light source.

15 2. The light shutter device according to claim 1, wherein:

the light source comprises:

a lamp; and

a multiple color filter which is located between the lamp and the light shutter elements; and

20 by switching the multiple color filter in order, the light incident to the light shutter elements is switched between a plurality of colors in order.

3. The light shutter device according to claim 1, wherein the driving
25 condition to be altered is a driving voltage applied to the light shutter elements.

4. The light shutter device according to claim 3, wherein:

the light shutter elements are driven by application of a voltage between a common electrode for all the light shutter elements and individual electrodes for the respective light shutter elements; and

5 the driving condition is altered by altering a potential of the common electrode to alter an electric field acting on the light shutter elements depending on the color of the light emitted from the light source.

10 5. The light shutter device according to claim 4, wherein the colors of the light emitted from the light source are three primary colors of red, green and blue.

15 6. The light shutter device according to claim 5, wherein the individual electrodes are set to have a potential corresponding to a half-wave voltage of the light shutter elements for red light.

20 7. The light shutter device according to claim 5, wherein the individual electrodes are set to have a potential corresponding to a half-wave voltage of the light shutter elements for blue light.

8. The light shutter device according to claim 5, wherein the individual electrodes are set to have a potential corresponding to a half-wave voltage of the light shutter elements for green light.

25 9. The light shutter device according to claim 3, wherein the driver inverts an electric field acting on the light shutter elements at specified

cycles.

10. The light shutter device according to claim 9, the electric field is inverted every after a cycle of switching the colors of the light from the
5 light source.

11. The light shutter device according to claim 3, wherein the driver superimposes a spike pulse voltage at a start of applying the driving voltage to the light shutter elements.

12. The light shutter device according to claim 9, wherein the driver superimposes a spike pulse voltage at a start of applying the driving voltage to the light shutter elements.

13. An array type writing device comprising:
15 a light source which emits light of a plurality of colors switching from one to another in order;

a plurality of light shutter elements made of a material with an electro-optical effect, said light shutter elements controlling in accordance
20 with image data whether to transmit or not to transmit the light which has been emitted from the light source and is incident to the light shutter elements; and

a driver for applying a voltage between a common electrode for all the light shutter elements and individual electrodes for the respective
25 light shutter elements to drive the light shutter elements, said driver setting the individual electrodes to have potentials in accordance with

image data and altering a driving condition of the common electrode in synchronization with switch of the colors of the light source.

14. The array type writing device according to claim 13, wherein the
5 individual electrodes are set to have a potential corresponding to a half-wave voltage for light of one of the colors emitted from the light source.

15. A method for driving a light shutter device, comprising the steps
of:

10 making light of a first color from a light source, which is capable of emitting light of a plurality of colors, incident to a plurality of light shutter elements made of a material with an electro-optical effect;

in synchronization with the incidence of the light of the first color to the light shutter elements, setting individual electrodes for the
15 respective light shutter elements to have potentials in accordance with image data by controlling a driver which drives the light shutter elements;

in synchronization with the incidence of the light of the first color to the light shutter elements, setting a common electrode for all the light
20 shutter elements to have a first potential by controlling the driver;

after the incidence of the light of the first color to the light shutter elements, making light of a second color from the light source incident to the light shutter elements;

in synchronization with the incidence of the light of the second
25 color to the light shutter elements, setting the individual electrodes to have potentials in accordance with image data by controlling the driver;

in synchronization with the incidence of the light of the second color to the light shutter elements, setting the common electrode to have a second potential which is different from the first potential by controlling the driver;

5 after the incidence of the light of the second color to the light shutter elements, making light of a third color from the light source incident to the light shutter elements;

10 in synchronization with the incidence of the light of the third color to the light shutter elements, setting the individual electrodes to have potentials in accordance with image data by controlling the driver; and

 in synchronization with the incidence of the light of the third color to the light shutter elements, setting the common electrode to have a third potential which is different from the first potential and from the second potential by controlling the driver.

15

16. The method according to claim 15, wherein the individual electrodes are set to have a potential corresponding to a half-wave voltage of the light shutter elements for light of one of the colors emitted from the light source.

20


17. The method according to claim 15, wherein the driver inverts an electric field acting on the light shutter elements at specified cycles.

18. The method according to claim 15, wherein the driver
25 superimposes a spike pulse voltage at a start of setting the individual electrodes and the common electrode to have the respective potentials.


ABSTRACT OF THE DISCLOSURE

While light of R, G and B is switched from one to another and directed to a plurality of light shutter elements made of PLZT, a voltage is
5 applied in accordance with image data between individual electrodes for the respective light shutter elements and a common electrode for all the light shutter elements. While a half-wave voltage V_r for light of R is applied to the individual electrodes, the voltage applied to the common electrode is altered to 0V, $V_r - V_g$ and $V_r - V_b$ in synchronization with switch
10 of the three primary colors so that half-wave voltages for the respective colors can be applied to the light shutter elements.


F / G. 1




F / G. 2




F / G. 3




F / G. 4




F / G. 7




F / G . 8



F I G . 9



F / G . 1 1



特許出願宣誓書および委任状

**DECLARATION AND POWER OF
ATTORNEY FOR PATENT APPLICATION**

私は、以下に記載された発明者として、こ
こに下記の通り宣言する：

As a below named inventor, I hereby declare
that:

私の住所、郵便の宛先、国籍は、私の氏名
の後に記載された通りである。

My residence, post office address, and
citizenship are as stated next to my name.

下記の名称の発明について、特許請求の範
囲に記載され、かつ特許が求められている発
明主題に関して、私は、私が最初、最先かつ
唯一の発明者である（唯一の氏名が記載され
ている場合）か、または、私と以下に記載さ
れた他の者が最初、最先かつ共同発明者であ
る（複数の氏名が記載されている場合）と、
信じている。

I believe that I am the original, first, and sole
inventor (if only one name is listed below) or I
and the other person(s) listed below are the
original, first, and joint inventors (if plural names
are listed below) of the subject matter which is
claimed and for which a patent is sought on the
invention entitled

LIGHT SHUTTER DEVICE AND A DRIVING METHOD THEREOF

上記発明の明細書はここに添付されているが
、下記のボックスがチェックされている場合
は、この限りでない：

the specification of which is attached hereto
unless the following box is checked:

☐ 上記発明が、以下の日に出願され、

☐ was filed on

以下の米国出願番号を有し、

as United States Application Number

または、以下のPCT国際出願番号を有し、

or PCT International Application Number

かつ、以下の日に補正されている

and was amended on

(該当する場合)。

(if applicable).

私は、上記の補正書によって補正された、特許請求の範囲を含む上記明細書を検討し、かつ内容を理解していることをここに表明する。

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above.

私は、連邦規則法典第37編規則1.56に定義されている、特許性について重要な情報を開示する義務があることを認める。

I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, Section 1.56.

私は、ここに、以下に記載した外国での特許出願または発明者証の出願、或いは米国以外の少なくとも一国を指定している米国法典第35編第365条(a)項によるPCT国際出願について、同第119条(a)-

(d)項または第365条(b)項に基づいて優先権を主張するとともに、優先権を主張する本出願の出願日より前の出願日を有する外国での特許出願または発明者証の出願、或いはPCT国際出願については、いかなる出願も、下記のボックスをチェックすることにより示した。

I hereby claim foreign priority under Title 35, United States Code, Section 119(a)-(d) or 365(b) of any foreign application(s) for patent or inventor's certificate, or 365(a) of any PCT international application which designated at least one country other than the United States listed below and have also identified below, by checking the box, any foreign application for patent or inventor's certificate, or PCT international application having a filing date before that of the application on which priority is claimed.

PRIOR FOREIGN APPLICATION(S)
(外国での先行出願)

Priority
Not Claimed
(優先権主張なし)

11-266829 JAPAN 21 September, 1999
(Number) (Country) (Day/Month/Year Filed)
(番号) (国名) (出願日/月/年)

☐

(Number) (Country) (Day/Month/Year Filed)
(番号) (国名) (出願日/月/年)

☐

(Number) (Country) (Day/Month/Year Filed)
(番号) (国名) (出願日/月/年)

☐

(Number) (Country) (Day/Month/Year Filed)
(番号) (国名) (出願日/月/年)

☐

(Number) (Country) (Day/Month/Year Filed)
(番号) (国名) (出願日/月/年)

☐

(Number) (Country) (Day/Month/Year Filed)
(番号) (国名) (出願日/月/年)

☐

(Number) (Country) (Day/Month/Year Filed)
(番号) (国名) (出願日/月/年)

☐

私は、ここに、下記のいかなる米国仮特許
出願についても、その米国法典第35編119
条(e)項の利益を主張する。

I hereby claim the benefit under Title 35,
United States Code, Section 119(e) of any United
States provisional application(s) listed below.

(Application Number)
(出願番号)

(Filing Date)
(出願日)

(Application Number)
(出願番号)

(Filing Date)
(出願日)

私は、ここに、以下のいかなる米国出願についても、その米国法典 35 編第 120 条に基づく利益を主張し、また米国を指定するいかなる PCT 国際出願についても、その同第 365 条(c)項に基づく利益を主張する。また、本出願の各特許請求の範囲の主題が、米国法典第 35 編第 112 条第 1 段に規定された態様で、先行する米国出願または PCT 国際出願に開示されていない場合においては、その先行出願の出願日と本国内出願日または PCT 国際出願日との間の期間中に入手された情報で、連邦規則法典第 37 編規則 1.56 に定義された特許性に関わる重要な情報について開示義務があることを承認する。

I hereby claim the benefit under Title 35, United States Code, Section 120 of any United States application(s), or 365(c) of any PCT international application designating the United States, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT international application in the manner provided by the first paragraph of Title 35, United States Code, Section 112, I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, Section 1.56 which became available between the filing date of the prior application and the national or PCT international filing date of application.

(Application Number) (出願番号)	(Filing Date) (出願日)	(Status: Patented, Pending, Abandoned) (現状：特許許可、係属中、放棄)
(Application Number) (出願番号)	(Filing Date) (出願日)	(Status: Patented, Pending, Abandoned) (現状：特許許可、係属中、放棄)

私は、ここに表明された私自身の知識に係る陳述が真実であり、かつ情報と信ずることに基づく陳述が、真実であると信じられることを宣言し、さらに、故意に虚偽の陳述などを行なった場合は、米国法典第 18 編第 1001 条に基づき、罰金または拘禁、若しくはその両方により処罰され、またそのような故意による虚偽の陳述は、本出願またはそれに対して発行されるいかなる特許も、その有効性に問題が生ずることを理解した上で陳述

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or

が行なわれたことを、ここに宣言する。

any patent issued thereon.

委任状： 私は、本出願を審査する手続きを行ない、かつ米国特許商標庁との全ての業務を遂行するために、記名された発明者として、以下のカスタマー番号に対応する弁護士・弁理士を任命する。また、私は、全ての連絡はそのカスタマー番号に対応するアドレスになされることを指示する。

POWER OF ATTORNEY: As a named inventor, I hereby appoint the practitioners associated with the Customer Number provided below to prosecute this application and transact all business in the Patent and Trademark Office connected therewith, and direct that all correspondence be addressed to the address associated with that Customer Number.

Customer Number: 24367



24367

PATENT & TRADEMARK OFFICE

直通電話先:

Direct telephone calls to:

James W. Williams

James W. Williams

ダイレクトイン: (214) 981-3328

Direct No.: (214) 981-3328

代表電話番号: (214) 981-3300

Main No.: (214) 981-3300

代理人の案件番号: 15162/02500

Attorney Docket No.: 15162/02500

Full name of sole or first joint inventor:
唯一または第 1 発明者の氏名:

Tsukasa		YAGI
First	Middle	Last
(名)	(ミドルネーム)	(姓)

Inventor's signature: _____
発明者の署名:

Date: _____
日付:

Residence:	Osaka-Shi	Osaka	Japan
住所:	(City)	(Prefecture)	(Country)
	(市)	(都道府県)	(国名)

Citizenship: Japanese
国籍

Post Office Address: c/o MINOLTA CO., LTD.
郵便の宛先:

<u>Osaka Kokusai Bldg., 3-13, 2-Chome,</u>
<u>Azuchi-Machi, Chuo-Ku, Osaka-Shi,</u>
<u>Osaka 541-8556 JAPAN</u>

Full name of second joint inventor:
第2共同発明者の氏名:

Ken		MATSUBARA
First	Middle	Last
(名)	(ミドルネーム)	(姓)

Inventor's signature: _____
発明者の署名:

Date: _____
日付:

Residence:	Osaka-Shi	Osaka	Japan
住所:	(City)	(Prefecture)	(Country)
	(市)	(都道府県)	(国名)

Citizenship: Japanese _____
国籍

Post Office Address: _____ c/o MINOLTA CO., LTD.
郵便の宛先:

Osaka Kokusai Bldg., 3-13, 2-Chome.
Azuchi-Machi, Chuo-Ku, Osaka-Shi,
Osaka 541-8556 JAPAN

Full name of third joint inventor:
第2共同発明者の氏名:

Tatsuya		KANAZAWA
First	Middle	Last
(名)	(ミドルネーム)	(姓)

Inventor's signature: _____
発明者の署名:

Date: _____
日付:

Residence:	Osaka-Shi	Osaka	Japan
住所:	(City)	(Prefecture)	(Country)
	(市)	(都道府県)	(国名)

Citizenship: Japanese _____
国籍

Post Office Address: _____ c/o MINOLTA CO., LTD.
郵便の宛先:

Osaka Kokusai Bldg., 3-13, 2-Chome,
Azuchi-Machi, Chuo-Ku, Osaka-Shi,
Osaka 541-8556 JAPAN

Full name of fourth joint inventor:

第2共同発明者の氏名:

Tomohiko		MASUDA
First	Middle	Last
(名)	(ミドルネーム)	(姓)

Inventor's signature: _____
発明者の署名:

Date: _____
日付:

Residence:	Osaka-Shi	Osaka	Japan
住所:	(City)	(Prefecture)	(Country)
	(市)	(都道府県)	(国名)

Citizenship: Japanese _____
国籍

Post Office Address: c/o MINOLTA CO., LTD. _____
郵便の宛先:

Osaka Kokusai Bldg., 3-13, 2-Chome, _____
Azuchi-Machi, Chuo-Ku, Osaka-Shi, _____
Osaka 541-8556 JAPAN _____